

# New Jersey Semi-Conductor Products, Inc.

20 STERN AVE.  
SPRINGFIELD, NEW JERSEY 07081  
U.S.A.

TELEPHONE: (973) 376-2922  
(212) 227-6005  
FAX: (973) 376-8960

**2N5202**

## DESCRIPTION

- Collector-emitter sustaining voltage  $V_{CEO(SUS)} = 90V(\text{Min})$
- High saturation voltage
- Wide area of safe operation

## APPLICATIONS



- Designed for use in high-current, high-speed switching circuits such as: low-distortion power amplifiers, oscillators, switching regulators, series regulators, converters, and inverters.

## ABSOLUTE MAXIMUM RATINGS ( $T_a=25^\circ\text{C}$ )

SYMBOL	PARAMETER	VALUE	UNIT
$V_{CBO}$	Collector-Base Voltage	100	V
$V_{CEO(SUS)}$	Collector-Emitter Voltage	50	V
$V_{CE(SUS)}$	Collector-Emitter Voltage $R_{BE} = 50 \Omega$	75	V
$V_{EBO}$	Emitter-Base Voltage	6	V
$I_C$	Collector Current-Continuous	4	A
$I_{CM}$	Collector Current-Peak	5	A
$I_E$	Base Current-Continuous	2	A
$P_D$	Total Power Dissipation@ $T_c=25^\circ\text{C}$	35	W
$T_J$	Junction Temperature	-65~200	°C
$T_{Stg}$	Storage Temperature	-65~235	°C

## THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	MAX	UNIT
$R_{Th(j-c)}$	Thermal Resistance, Junction to Case	5.0	°C/W



# New Jersey Semi-Conductor Products, Inc.

20 STERN AVE.  
SPRINGFIELD, NEW JERSEY 07081  
U.S.A.


TELEPHONE: (973) 376-2922  
(212) 227-6005  
FAX: (973) 376-8960

**2N5202**

## ELECTRICAL CHARACTERISTICS

T<sub>c</sub>=25°C unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	MAX	UNIT
V <sub>CEO(sus)</sub>	Collector-Emitter Sustaining Voltage	I <sub>C</sub> = 200mA; I <sub>B</sub> = 0	50		V
V <sub>CER(sus)</sub>	Collector-Emitter Sustaining Voltage	I <sub>C</sub> = 200mA; I <sub>B</sub> = 0	75		V
V <sub>CE(sat)</sub>	Collector-Emitter Saturation Voltage	I <sub>C</sub> = 4A; I <sub>B</sub> = 0.4A		1.2	V
V <sub>BE(sat)</sub>	Base-Emitter Saturation Voltage	I <sub>C</sub> = 4A; I <sub>B</sub> = 0.4A		2.0	V
I <sub>CEO</sub>	Collector Cutoff Current	V <sub>CE</sub> = 70V; I <sub>B</sub> = 0		10	mA
I <sub>ESO</sub>	Emitter Cutoff Current	V <sub>EB</sub> = 6V; I <sub>C</sub> = 0		10	mA
h <sub>FE1</sub>	DC Current Gain	I <sub>C</sub> = 0.5A; V <sub>CE</sub> = 10V	6		
h <sub>FE2</sub>	DC Current Gain	I <sub>C</sub> = 4A; V <sub>CE</sub> = 1.2V	10	100	



**Quality Semi-Conductors**