

New Jersey Semi-Conductor Products, Inc.

20 STERN AVE.
SPRINGFIELD, NEW JERSEY 07081
U.S.A.

TELEPHONE: (973) 376-2922
(212) 227-6005
FAX: (973) 376-8960

Silicon NPN Power Transistors

2N6654

DESCRIPTION

- With TO-3 package
- High voltage capability
- Fast switching speeds
- Low saturation voltage

APPLICATIONS

- Switching regulators
- Inverters
- Solenoid and relay drivers
- Deflection circuits

PINNING (See Fig.2)

PIN	DESCRIPTION
1	Base
2	Emitter
3	Collector




Fig.1 simplified outline (TO-3) and symbol

MAXIMUM RATINGS(T_a=25°C)

SYMBOL	PARAMETER	CONDITIONS	VALUE	UNIT
V _{CBO}	Collector-base voltage	Open emitter	500	V
V _{CEO}	Collector-emitter voltage	Open base	350	V
V _{EBO}	Emitter-base voltage	Open collector	6	V
I _c	Collector current		20	A
I _{CM}	Collector current-peak		30	A
P _T	Total power dissipation	T _c =25°C	150	W
T _j	Junction temperature		200	°C
T _{stg}	Storage temperature		-65~200	°C

THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	MAX	UNIT
R _{thJ-C}	Thermal resistance from junction to case	1.0	°C/W

Silicon NPN Power Transistors

2N6654

CHARACTERISTICS

T_j=25°C unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
V _{CEO(SUS)}	Collector-emitter sustaining voltage	I _C =0.1A; I _B =0	350			V
V _{(BR)CBO}	Collector-emitter breakdown voltage	I _C =1mA; I _E =0	500			V
V _{CEsat-1}	Collector-emitter saturation voltage	I _C =10A; I _B =2A		1.8		V
V _{CEsat-2}	Collector-emitter saturation voltage	I _C =15A; I _B =3A		2.2		V
V _{BEsat}	Base-emitter saturation voltage	I _C =15A; I _B =3A		1.8		V
I _{CEV}	Collector cut-off current	V _{CE} =500V; V _{BE(off)} =-1.5V T _C =150°C		0.1 2.0		mA
I _{EBO}	Emitter cut-off current	V _{EB} =6V; I _C =0		0.1		mA
h _{FE-1}	DC current gain	I _C =1A; V _{CE} =5V	15		50	
h _{FE-2}	DC current gain	I _C =10A; V _{CE} =15V	10			

