

*New Jersey Semi-Conductor Products, Inc.*

20 STERN AVE.  
 SPRINGFIELD, NEW JERSEY 07081  
 U.S.A.

TELEPHONE: (973) 376-2922  
 (212) 227-6005  
 FAX: (973) 376-8960

ELECTRICAL CHARACTERISTICS ( $T_A=25^{\circ}C$  unless otherwise noted)

PARAMETER	SYMBOL	BC440 BC460		BC441 BC461		UNIT	TEST CONDITIONS
		MIN	MAX	MIN	MAX		
Collector-Emitter Breakdown Voltage	$V_{CE0} *$	40		60		V	$I_C=100mA$ $I_B=0$
Emitter-Base Breakdown Voltage	$V_{EB0}$	5		5		V	$I_E=0.1mA$ $I_C=0$
Collector Cutoff Current	$I_{CBO}$		100		100	nA	$V_{CB}=40V$ $I_E=0$
Collector Cutoff Current	$I_{CER}$		10		10	$\mu A$	$V_{CE}=50V$ $R_{BE}=100\Omega$
Collector-Emitter Saturation Voltage	$V_{CE(sat)} *$		1		1	V	$I_C=1A$ $I_B=0.1A$
Base-Emitter Saturation Voltage	$V_{BE(sat)} *$		1.5		1.5	V	$I_C=1A$ $I_B=0.1A$
D.C. Current Gain	$H_{FE} *$	40	250	40	250	V	$I_C=500mA$ $V_{CE}=4V$
	Group 4	40	70	40	70		
	Group 5	60	130	60	130		
	Group 6	115	250	115	250		
		20					$I_C=1A$ $V_{CE}=2V$
Current Gain-Bandwidth Product	$f_T$	50		50		MHz	$I_C=50mA$ $V_{CE}=4V$
Collector-Base Capacitance	$C_{ob}$		25		25	pF	$V_{CB}=10V$ $I_E=0$ $f=1MHz$

\* Pulse Test : Pulse Width=0.3ms, Duty Cycle=1%

CASE TO-39



Quality Semi-Conductors

ABSOLUTE MAXIMUM RATINGS

		<u>BC440(NPN)</u> <u>BC460(PNP)</u>	<u>BC441(NPN)</u> <u>BC461(PNP)</u>
Collector-Emitter Voltage ( $R_{BE} \leq 100 \Omega$ )	$V_{CE}$	50V	75V
Collector-Emitter Voltage ( $I_B=0$ )	$V_{CEO}$	40V	60V
Emitter-Base Voltage	$V_{EB}$	5V	5V
Collector Current	$I_C$		1A
Collector Peak Current	$I_{CM}$		2A
Total Power Dissipation ( $T_C \leq 25^\circ C, V_{CE} \leq 10V$ ) ( $T_A \leq 25^\circ C$ )	$P_{tot}$		10W 1W
Operating Junction & Storage Temperature	$T_j, T_{stg}$		-55 to 200°C